

AXOR 4028 T (4x2) M/T



Specification / Spesifikasi		MB 4028 T
Wheel & Rim / Roda & Ban	Rim size / Ukuran roda	7.50 x 20
	Tyre size / Ukuran ban	11.00 R 20
Engine/ Mesin	Type / Tipe	OM 906 LA, 6 Cylinder
	Cylinder volume / Volume silinder	(liter) 6.37
	Max. power / Kekuatan maksimum	(ps/rpm) 280 / 2,200
	Max. torque / Torsi maksimum	(Nm/rpm) 1,100 @ 1200 -1,600
Transmission / Transmisi	Model	G 131 - 9 / 14.57-1.0
	Type / Tipe	Manual
	Total gears / Total gigi	9 speed forward + 1 speed reverse
Performance / Performa	Max. speed / Kecepatan maksimum	(km/h) 90
	Gradeability / Kemampuan menanjak	% 33 (Crawler)
Accu / Aki		2 x 12V, 120 Ah
Clutch/Kopling	Type / Tipe	Dry-single plate
	Diameter	(mm) 430
Fuel tank / Volume tangki BBM		380 (with additional 200)
Front Axle / Sumbu depan	Max. capacity / Kapasitas beban maksimum	(kg) 6,600
	Max. capacity / Kapasitas beban maksimum	(kg) 11,000
Rear Axle / Sumbu belakang	Final gear ratio / Perbandingan gigi terakhir	4.3
	Diff. lock	Inter-wheel
	Front / Depan	Parabolic with stabilizer
Suspension / Suspensi	Rear / Belakang	Semi-elliptic with auxiliary spring
	5 th Wheel Coupling	2" Kingpin, 350 mm
Brake / Rem	Main brake / Rem utama	Full air S-cam dual circuit
	Additional Brake / Rem tambahan	ABS, engine & exhaust brake, Trailer brake
Dimension/ Dimensi	Wheelbase / Jarak sumbu roda	(mm) 3,600
	Distance between rear axles / Jarak sumbu roda belakang	(mm) -
	Total length / Panjang total	(mm) 6,100
	Total width / Lebar total	(mm) 2,500
	Total height / Tinggi total	(mm) 3,100
	Front overhang (FOH) / Julur depan	(mm) 1,500
	Rear overhang (ROH) / Julur belakang	(mm) 1,000
	Turning circle radius / Radius putar	(mm) 6,550
	Ground clearance / Jarak terendah ke tanah	(mm) 260
Chassis weight / Berat chassis	Front axle / Sumbu depan	(kg) 4,225
	Rear axle / Sumbu belakang	(kg) 2,610
	Kerb weight / Berat kosong	(kg) 6,835
	GVW / JBB	(kg) 16,000
	GCW / JBI	(kg) 37,000

